



## Surge Protective Device

---

| WTH-20/D/R Series                                |    |
|--|----|
| Paperless Datasheet                              | 01 |
| Model & Ordering Code                            | 01 |
| Certificates of Products                         | 01 |
| More Package                                     | 02 |
|  |    |
| Technical Data                                   | 03 |
| Surge Protection Connection Diagram              | 04 |
| Dimensions                                       | 04 |
| Remote Contacts (Dry Contacts)                   | 05 |
| Fault Indication                                 | 05 |
|  |    |
| Common Terms and Definitions                     | 06 |
| How to choose a suitable $U_c$ (MCOV) value      | 06 |
| AC Network Connection Diagram                    | 07 |
| Difference mode & Common mode Connection Diagram | 08 |
| Selection of back-up fuse                        | 09 |
| Selection of back-up circuit-breaker             | 09 |
| Application                                      | 10 |
|  |    |
| N-PE Module                                      | 11 |
| 3P + NPE Combintion Package                      | 11 |
| 1P + NPE Combintion Package                      | 11 |
|  |    |
| FAQ & Help                                       | 12 |
| Download WatchfulEyE Official App                | 13 |
| After-sale Services                              | 13 |
| I have a question                                | 13 |



## Surge Protective Device

### Paperless Datasheet

Going green and protecting environment is manufacturers' responsibility. Each WatchfulEyE product has a link of downloading data sheet on its enclosure:

<http://datasheet.watchfuleyesolutions.com/US120194.html>

### Model & Ordering Code

| Model             | Ordering Code | MCOV/Uc | Remote Contacts | UPC/EAN Code     |
|-------------------|---------------|---------|-----------------|------------------|
| WTH-20/D/R/1P-275 | US120194      | 275VAC  | YES             | (0) 811914031352 |
| WTH-20/D/1P-275   | US120184      |         | NO              | (0) 811914031413 |
| WTH-20/D/R/1P-320 | US120195      | 320VAC  | YES             | (0) 811914031369 |
| WTH-20/D/1P-320   | US120185      |         | NO              | (0) 811914031420 |
| WTH-20/D/R/1P-385 | US120196      | 385VAC  | YES             | (0) 811914031376 |
| WTH-20/D/1P-385   | US120186      |         | NO              | (0) 811914031437 |
| WTH-20/D/R/1P-420 | US120197      | 420VAC  | YES             | (0) 811914031383 |
| WTH-20/D/1P-420   | US120187      |         | NO              | (0) 811914031444 |



### Certificates of Products



LISTED  
E345944



RoHS

IEC61643-11



## Surge Protective Device

### More Package

|                   |                   |            |            |            |
|-------------------|-------------------|------------|------------|------------|
| Model with suffix | WTH-20/D/R/1P-275 | x2pcs      | x3pcs      | x4pcs      |
| Ordering Code     | US120194          | US120194x2 | US120194x3 | US120194x4 |

|                   |                 |            |            |            |
|-------------------|-----------------|------------|------------|------------|
| Model with suffix | WTH-20/D/1P-275 | x2pcs      | x3pcs      | x4pcs      |
| Ordering Code     | US120184        | US120184x2 | US120184x3 | US120184x4 |

|                   |                   |            |            |            |
|-------------------|-------------------|------------|------------|------------|
| Model with suffix | WTH-20/D/R/1P-320 | x2pcs      | x3pcs      | x4pcs      |
| Ordering Code     | US120195          | US120195x2 | US120195x3 | US120195x4 |

|                   |                 |            |            |            |
|-------------------|-----------------|------------|------------|------------|
| Model with suffix | WTH-20/D/1P-320 | x2pcs      | x3pcs      | x4pcs      |
| Ordering Code     | US120185        | US120185x2 | US120185x3 | US120185x4 |

|                   |                   |            |            |            |
|-------------------|-------------------|------------|------------|------------|
| Model with suffix | WTH-20/D/R/1P-385 | x2pcs      | x3pcs      | x4pcs      |
| Ordering Code     | US120196          | US120196x2 | US120196x3 | US120196x4 |

|                   |                 |            |            |            |
|-------------------|-----------------|------------|------------|------------|
| Model with suffix | WTH-20/D/1P-385 | x2pcs      | x3pcs      | x4pcs      |
| Ordering Code     | US120186        | US120186x2 | US120186x3 | US120186x4 |

|                   |                   |            |            |            |
|-------------------|-------------------|------------|------------|------------|
| Model with suffix | WTH-20/D/R/1P-420 | x2pcs      | x3pcs      | x4pcs      |
| Ordering Code     | US120197          | US120197x2 | US120197x3 | US120197x4 |

|                   |                 |            |            |            |
|-------------------|-----------------|------------|------------|------------|
| Model with suffix | WTH-20/D/1P-420 | x2pcs      | x3pcs      | x4pcs      |
| Ordering Code     | US120187        | US120187x2 | US120187x3 | US120187x4 |



## Surge Protective Device

### Description


In accordance with: IEC 61643-11 - Class III and UL1449 Type 4 Location  
Location of use: branch sub-distribution boards  
Plug-in module and separate base design enables convenient maintenance.  
Internal thermal disconnect devices help ensure safe or at end-of-life

### WTH-20/D/R/1P Series Technical Data

|                                      |  |
|--------------------------------------|--|
| Requirement Class to IEC61643-11     | Class III  |
| IEEE Category Rating                 | B & A  |
| Nominal Discharge Current (In)       | 10kA   |
| Max. Discharge Current (Imax)        | 20kA   |
| Open circuit voltage (Uoc)           | 20kV   |
| Protection Modes                     | L-PE, N-PE   |
| Protective Element                   | MOV  |
| Follow Current (If)                  | NO   |
| Response Time (tA)                   | <5ns   |
| Leakage Current (at 75%U1mA)         | <20μA  |
| Thermal Protection                   | YES  |
| Protection Rating (IP Code)          | IP 20  |
| Short Circuit Current Ratings (SCCR) | 25kA rms   |
| Max. Back-up Fuse (if mains >50A)    | 50A gL (circuit-breaker: <20A)                           |
| Surge Life at 3kA (8/20μs)           | >5000 events   |
| Temperature Range                    | - 40°F to 176°F (-40°C to 80°C)                          |
| Relative Humidity                    | 0% to 95% noncondensing                                  |
| Maximum Operating Altitude           | 10,000 feet (3000m)                                      |
| Terminal Cross Section               | 35mm <sup>2</sup> (solid) / 25mm <sup>2</sup> (stranded) |
| Stripping Length Contacts            | 0.6inches (15mm)   |
| Terminal Screw Torque                | Max. 3.5Nm   |
| DIN Rail EN60715                     | 35mm top-hat rail  |
| Dimensions DIN 43880                 | 18mm (1TE)   |
| Housing Material                     | Thermoplastic (UL94 V-0)                                 |
| Housing Design                       | Modular design   |
| Net Weight Per Unit                  | 0.3Lb (136g)   |


## Surge Protective Device

### Surge Protection Connection Diagram




|  |        |        |        |        |
|--|--------|--------|--------|--------|
| Maximum Continuous Operating Voltage (MCOV/Uc) | 275VAC | 320VAC | 385VAC | 420VAC |
| Voltage Protection Level (Up)                  | 1.3kV  | 1.4kV  | 1.5kV  | 1.7kV  |
| Residual Voltage (Ures)                        | 1.0kV  | 1.1kV  | 1.2kV  | 1.4kV  |

### Dimensions




### Remote Contacts (Dry Contacts)

- 1: COM (Common)
- 2: NC (Normally Close)
- 3: NO (Normally Open)



|                           |                         |
|---------------------------|-------------------------|
| Contact Ratings           | 125VAC/3A, 250VAC/1.5A  |
| Terminal Cross Section    | Max. 1.5mm <sup>2</sup> |
| Stripping Length Contacts | 0.25 inches (6-7mm)     |
| Remote Terminal Torque    | 0.25Nm                  |

### Fault Indication (same indication in 1P/2P/3P/4P/1P+NPE/3P+NPE models)





## Surge Protective Device

### Common Terms and Definitions

1. Normal operating voltage rating ( $U_n$ )

2. Maximum Continuous Operating Voltage ( $U_c$ /MCOV):

Maximum r.m.s. voltage, which may be continuously applied to the surge protective device's mode of protection.

3. Nominal Discharge Current for Class II Test ( $I_n$ ):

crest value of the current through the surge protective device having a current waveshape of 8/20 $\mu$ s.

4. Maximum Discharge Current ( $I_{max}$ ):

Crest value of a current through the surge protective device having an 8/20 $\mu$ s waveshape and magnitude according to the manufacturers specification.  $I_{max}$  is equal to or greater than  $I_n$ .

5. Voltage Protection Level ( $U_p$ ):

Maximum voltage to be expected at the surge protective device terminals due to an impulse stress with defined voltage steepness and an impulse stress with a discharge current with given amplitude and waveshape.

6. Residual Voltage ( $U_{res}$ ):

Crest value of voltage that appears between the terminals of an surge protective device due to the passage of discharge current.

7. IEEE 62.41

CATEGORY C: outdoor overhead lines, service entrance (most severe)

CATEGORY B: major feeder, short branch circuits, service panel (indoor)

CATEGORY A: long branch circuits, receptacles (indoor) (least severe)

### How to choose a suitable $U_c$ (MCOV) value

Note:  $U_c > 1.15U_n$

The relationship between two parameters  $U_c$  and  $U_p$  of a surge protective device is proportional.

If  $U_c$  is small, the value of  $U_p$  is also small; surge protective devices with smaller  $U_p$  can provide better surge protection.

Whether to choose smaller  $U_c$  depends on the voltage stability of the grid.

If you choose surge protective devices with smaller  $U_c$  for the grid with instable voltage, the surge protective devices will frequently work while the grid voltage fluctuates, resulting in shortening surge protective device's product life.


If you choose larger  $U_c$ , and the value of  $U_p$  is accordingly large, the surge protective efficiency will not be so fine.

If you are unsure of the voltage stability of the grid,

it is suggested to calculate MCOV( $U_c$ ) using the following formula:  $\sqrt{2} U_n < U_c < \sqrt{3} U_n$

| AC Network ( $U_n$ ) | MCOV( $U_c$ ), L/N-PE Protection Mode |
|----------------------|---------------------------------------|
| 110V                 | 150V                                  |
| 120/208V             | 150V                                  |
| 127/220V             | 150V                                  |
| 220/380V             | 275V, 320V, 385V                      |
| 230/400V             | 275V, 320V, 385V, 420V                |
| 240/415V             | 320V, 385V, 420V                      |
| 277/480V             | 320V, 385V, 420V                      |
| 347/600V             | 550V, 690V                            |


### AC Network Connection Diagram (1/2)






### AC Network Connection Diagram (2/2)

6




AC System Voltage

L-L:  
240V  
480V  
600V





7




AC System Voltage

L-N/L-L:  
120/240V  
240/480V





### Difference mode & Common mode Connection Diagram

8



AC System Voltage


L-N:  
110V, 120V, 127V  
220V, 230V, 240V  
277V, 480V




**Common mode:** L-PE, N-PE surge protection

**Difference mode:** L-N surge protection

### Selection of back-up fuse




### Selection of back-up circuit-breaker



## Surge Protective Device

### Application



### Key

1. Origin of the installation
  2. Distribution board
  3. Distribution outlet
  4. Main earthing terminal or bar
  5. Surge protective device, class I or II tested
  6. Earthing connection (earthing conductor) of the surge protective device
  7. Fixed equipment to be protected
  8. Surge protective device, class II tested
  9. Surge protective device, class II or class III tested
  10. Decoupling element or line length
- F1, F2, F3 overcurrent protective disconnectors
- NOTE Refer to IEC 61643-12 for further information.



## Surge Protective Device

### N-PE Module

WTH-65/G module integrates High-Energy GDT, no leakage current. It pairs WTH-20/D/R series surge protector, combined into N-PE protection mode, the two modules are the same in dimension and shape, and are connected with a dedicated bus-bar to achieve a perfect combination.

#### WTH-65/G Technical Data

|  |                 |
|--|-----------------|
| Max. continuous operating voltage (Uc) | 255V            |
| Nominal Discharge Current (In)         | 25kA            |
| Max. Discharge Current (Imax)          | 65kA            |
| Pulsed Current (Iimp)                  | 15kA            |
| Voltage protection level (Up)          | 1.0kV           |
| Protection Modes                       | N-PE only       |
| Protective Element                     | High Energy GDT |
| Follow Current (If)                    | 100A rms        |
| Response Time (tA)                     | <100ns          |
| Net Weight Per Unit                    | 0.24Lb (109g)   |

### 3P + NPE Combintion Package

| Model with suffix            | Ordering Code | Model with suffix          | Ordering Code |
|------------------------------|---------------|----------------------------|---------------|
| WTH-20/D/R/1P-275 x3pcs +NPE | US120194x3N   | WTH-20/D/1P-275 x3pcs +NPE | US120184x3N   |
| WTH-20/D/R/1P-320 x3pcs +NPE | US120195x3N   | WTH-20/D/1P-320 x3pcs +NPE | US120185x3N   |
| WTH-20/D/R/1P-385 x3pcs +NPE | US120196x3N   | WTH-20/D/1P-385 x3pcs +NPE | US120186x3N   |
| WTH-20/D/R/1P-420 x3pcs +NPE | US120197x3N   | WTH-20/D/1P-420 x3pcs +NPE | US120187x3N   |

### 1P + NPE Combintion Package

| Model with suffix      | Ordering Code | Model with suffix    | Ordering Code |
|------------------------|---------------|----------------------|---------------|
| WTH-20/D/R/1P-275 +NPE | US120194x1N   | WTH-20/D/1P-275 +NPE | US120184x1N   |
| WTH-20/D/R/1P-320 +NPE | US120195x1N   | WTH-20/D/1P-320 +NPE | US120185x1N   |
| WTH-20/D/R/1P-385 +NPE | US120196x1N   | WTH-20/D/1P-385 +NPE | US120186x1N   |
| WTH-20/D/R/1P-420 +NPE | US120197x1N   | WTH-20/D/1P-420 +NPE | US120187x1N   |



## Surge Protective Device

---

### FAQ & Help

1. What should I do if I can't find the paper manual in the product packaging?

Watchful Eye products is committed to going green with paperless data sheets. On the side of each product enclosure is an engraved link with URL for downloading paperless data sheet and QR code of the website. If you need the paper data sheet, you can open the link and print the data sheet by yourself.

2. The advantages of fault indication windows?

If surge protection fails, the fault indication windows will turn red, thus it can be seen intuitively, and the surge protective device can be replaced in time to avoid damage to the equipment caused by a second surge.

3. What instruments can be used to test whether its surge protection function is normal or not?

Test with a Watchful Eye surge protector tester

4. Can you list more applications?

Power supply panel, whole house



## Surge Protective Device

---

### Download WatchfulEye Official App

To learn about more products and updates from company, please scan QR code to download the official App:



---

### After-sale Services

Watchful Eye provides a 5-year quality warranty globally.

[I have a question](#)