



## Surge Protective Device

---

WTH-165/B/R Series	
Paperless Datasheet	01
Model & Ordering Code	01
Certificates of Products	01
More Package	02
Technical Data	03
Surge Protection Connection Diagram	04
Dimensions	04
Remote Contacts (Dry Contacts)	05
Fault Indication	05
Common Terms and Definitions	06
How to choose a suitable $U_c$ (MCOV) value	06
AC Network Connection Diagram	07
Difference mode & Common mode Connection Diagram	08
Selection of back-up fuse	09
Selection of back-up circuit-breaker	09
Application	10
N-PE Module	11
3P + NPE Combintion Package	11
1P + NPE Combintion Package	11
FAQ & Help	12
Download WatchfulEyE Official App	13
After-sale Services	13
I have a question	13



## Surge Protective Device

### Paperless Datasheet

Going green and protecting environment is manufacturers' responsibility. Each WatchfulEyE product has a link of downloading data sheet on its enclosure:

<http://datasheet.watchfuleyesolutions.com/US120324.html>

### Model & Ordering Code

Model	Ordering Code	MCOV/Uc	Remote Contacts	UPC/EAN Code
WTH-165/B/R/1P-275	US120324	275VAC	YES	(0) 811914031000
WTH-165/B/1P-275	US120314		NO	(0) 811914031055
WTH-165/B/R/1P-320	US120325	320VAC	YES	(0) 811914031017
WTH-165/B/1P-320	US120315		NO	(0) 811914031062
WTH-165/B/R/1P-385	US120326	385VAC	YES	(0) 811914031024
WTH-165/B/1P-385	US120316		NO	(0) 811914031079
WTH-165/B/R/1P-420	US120327	420VAC	YES	(0) 811914031031
WTH-165/B/1P-420	US120317		NO	(0) 811914031086



### Certificates of Products



LISTED  
E345944



RoHS

IEC61643-11

Note: MCOV 385VAC UL listed only



## Surge Protective Device

### More Package

Model with suffix	WTH-165/B/R/1P-275	x2pcs	x3pcs	x4pcs
Ordering Code	US120324	US120324x2	US120324x3	US120324x4

Model with suffix	WTH-165/B/1P-275	x2pcs	x3pcs	x4pcs
Ordering Code	US120314	US120314x2	US120314x3	US120314x4

Model with suffix	WTH-165/B/R/1P-320	x2pcs	x3pcs	x4pcs
Ordering Code	US120325	US120325x2	US120325x3	US120325x4

Model with suffix	WTH-165/B/1P-320	x2pcs	x3pcs	x4pcs
Ordering Code	US120315	US120315x2	US120315x3	US120315x4

Model with suffix	WTH-165/B/R/1P-385	x2pcs	x3pcs	x4pcs
Ordering Code	US120326	US120326x2	US120326x3	US120326x4

Model with suffix	WTH-165/B/1P-385	x2pcs	x3pcs	x4pcs
Ordering Code	US120316	US120316x2	US120316x3	US120316x4

Model with suffix	WTH-165/B/R/1P-420	x2pcs	x3pcs	x4pcs
Ordering Code	US120327	US120327x2	US120327x3	US120327x4

Model with suffix	WTH-165/B/1P-420	x2pcs	x3pcs	x4pcs
Ordering Code	US120317	US120317x2	US120317x3	US120317x4



## Surge Protective Device

### Description

In accordance with: IEC 61643-11 - Class I and UL1449 Type 4 Location

Location of use: main sub-distribution boards


One-piece compact design with minimized volume but maximized capability of Class I surge protection.

Internal thermal disconnect devices help ensure safe or at end-of-life

### WTH-165/B/R/1P Series Technical Data

Requirement Class to IEC61643-11	Class I
IEEE Category Rating	C & B
Nominal Discharge Current (In)	80kA
Max. Discharge Current (Imax)	165kA
Pulsed Current (Iimp)	17.5kA
Protection Modes	L-PE, N-PE
Protective Element	High Energy MOV
Follow Current (If)	NO
Response Time (tA)	<5ns
Leakage Current (at 75%U1mA)	<20μA
Thermal Protection	YES
Protection Rating (IP Code)	IP 20
Short Circuit Current Ratings (SCCR)	25kA rms
Max. Back-up Fuse (if mains >160A)	160A gL (circuit-breaker: <100A)
Surge Life at 3kA (8/20μs)	>5000 events
Temperature Range	- 40°F to 176°F (-40°C to 80°C)
Relative Humidity	0% to 95% noncondensing
Maximum Operating Altitude	10,000 feet (3000m)
Terminal Cross Section	35mm <sup>2</sup> (solid) / 25mm <sup>2</sup> (stranded)
Stripping Length Contacts	0.6inches (15mm)
Terminal Screw Torque	Max. 3.5Nm
DIN Rail EN60715	35mm top-hat rail
Dimensions DIN 43880	36mm (2TE)
Housing Material	Thermoplastic (UL94 V-0)
Housing Design	One-piece compact design
Net Weight Per Unit	0.46Lb (209g)

### Surge Protection Connection Diagram




Indication of three levels of surge protection

With three MOVs' protection at the same time, the module can realize Class I surge protection; in case that two of the indicator windows indicates red, it can still meet Class II surge protection requirements.


Maximum Continuous Operating Voltage (MCOV/Uc)	275VAC	320VAC	385VAC	420VAC
Voltage Protection Level (Up)	2.1kV	2.2kV	2.4kV	2.5kV
Residual Voltage (Ures)	1.0kV	1.1kV	1.2kV	1.4kV

### Dimensions




### Remote Contacts (Dry Contacts)

- 1: COM (Common)
- 2: NC (Normally Close)
- 3: NO (Normally Open)



Contact Ratings	125VAC/3A, 250VAC/1.5A
Terminal Cross Section	Max. 1.5mm <sup>2</sup>
Stripping Length Contacts	0.25 inches (6-7mm)
Remote Terminal Torque	0.25Nm

### Fault Indication





## Surge Protective Device

### Common Terms and Definitions

1. Normal operating voltage rating ( $U_n$ )

2. Maximum Continuous Operating Voltage ( $U_c$ /MCOV):

Maximum r.m.s. voltage, which may be continuously applied to the surge protective device's mode of protection.

3. Nominal Discharge Current for Class II Test ( $I_n$ ):

crest value of the current through the surge protective device having a current waveshape of  $8/20\mu s$ .

4. Maximum Discharge Current ( $I_{max}$ ):

Crest value of a current through the surge protective device having an  $8/20\mu s$  waveshape and magnitude according to the manufacturers specification.  $I_{max}$  is equal to or greater than  $I_n$ .

5. Voltage Protection Level ( $U_p$ ):

Maximum voltage to be expected at the surge protective device terminals due to an impulse stress with defined voltage steepness and an impulse stress with a discharge current with given amplitude and waveshape.

6. Residual Voltage ( $U_{res}$ ):

Crest value of voltage that appears between the terminals of an surge protective device due to the passage of discharge current.

7. IEEE 62.41

CATEGORY C: outdoor overhead lines, service entrance (most severe)

CATEGORY B: major feeder, short branch circuits, service panel (indoor)

CATEGORY A: long branch circuits, receptacles (indoor) (least severe)

### How to choose a suitable $U_c$ (MCOV) value

Note:  $U_c > 1.15U_n$

The relationship between two parameters  $U_c$  and  $U_p$  of a surge protective device is proportional.

If  $U_c$  is small, the value of  $U_p$  is also small; surge protective devices with smaller  $U_p$  can provide better surge protection.

Whether to choose smaller  $U_c$  depends on the voltage stability of the grid.

If you choose surge protective devices with smaller  $U_c$  for the grid with instable voltage, the surge protective devices will frequently work while the grid voltage fluctuates, resulting in shortening surge protective device's product life.

If you choose larger  $U_c$ , and the value of  $U_p$  is accordingly large, the surge protective efficiency will not be so fine.

If you are unsure of the voltage stability of the grid,

it is suggested to calculate MCOV( $U_c$ ) using the following formula:  $\sqrt{2} U_n < U_c < \sqrt{3} U_n$

AC Network ( $U_n$ )	MCOV( $U_c$ ), L/N-PE Protection Mode
110V	150V
120/208V	150V
127/220V	150V
220/380V	275V, 320V, 385V
230/400V	275V, 320V, 385V, 420V
240/415V	320V, 385V, 420V
277/480V	320V, 385V, 420V
347/600V	550V, 690V

### AC Network Connection Diagram (1/2)


1




#### AC System Voltage

L-N:  
110V, 120V, 127V  
220V, 230V, 240V  
277V, 480V


#### 2P Combination



#### 1P+NPE Combination




2




#### AC System Voltage

L-N/L-L:  
120/240V  
127/254V  
240/480V  
277/480V


#### 3P Combination



#### 2P Combination




3




#### AC System Voltage

L-N/L-L:  
120V/208Y  
127V/220Y  
220V/380Y  
230V/400Y  
240V/415Y  
277V/480Y  
347V/600Y


#### 4P Combination



#### 3P+NPE Combination




4




#### AC System Voltage

L-L:  
480V

#### 3P Combination




5



#### AC System Voltage

L-L:  
240V  
480V  
600V


#### 3P Combination






### AC Network Connection Diagram (2/2)

6




AC System Voltage

L-L:  
240V  
480V  
600V





7




AC System Voltage

L-N/L-L:  
120/240V  
240/480V





### Difference mode & Common mode Connection Diagram

8



AC System Voltage


L-N:  
110V, 120V, 127V  
220V, 230V, 240V  
277V, 480V




**Common mode:** L-PE, N-PE surge protection

**Difference mode:** L-N surge protection

### Selection of back-up fuse




### Selection of back-up circuit-breaker



## Surge Protective Device

### Application



### Key

1. Origin of the installation
  2. Distribution board
  3. Distribution outlet
  4. Main earthing terminal or bar
  5. Surge protective device, class I or II tested
  6. Earthing connection (earthing conductor) of the surge protective device
  7. Fixed equipment to be protected
  8. Surge protective device, class II tested
  9. Surge protective device, class II or class III tested
  10. Decoupling element or line length
- F1, F2, F3 overcurrent protective disconnectors
- NOTE Refer to IEC 61643-12 for further information.



## Surge Protective Device

### N-PE Module

WTH-165/G module integrates High-Energy GDT, no leakage current. It pairs WTH-165/B/R series surge protector, combined into N-PE protection mode, the two modules are the same in dimension and shape, and are connected with a dedicated bus-bar to achieve a perfect combination.

#### WTH-165/G Technical Data

Max. continuous operating voltage (Uc)	255V
Nominal Discharge Current (In)	80kA
Max. Discharge Current (Imax)	165kA
Pulsed Current (Iimp)	52.5kA
Voltage protection level (Up)	1.5kV
Protection Modes	N-PE only
Protective Element	High Energy GDT
Follow Current (If)	100A rms
Response Time (tA)	<100ns
Net Weight Per Unit	0.4Lb (180g)

### 3P + NPE Combintion Package

Model with suffix	Ordering Code	Model with suffix	Ordering Code
WTH-165/B/R/1P-275 x3pcs +NPE	US120324x3N	WTH-165/B/1P-275 x3pcs +NPE	US120314x3N
WTH-165/B/R/1P-320 x3pcs +NPE	US120325x3N	WTH-165/B/1P-320 x3pcs +NPE	US120315x3N
WTH-165/B/R/1P-385 x3pcs +NPE	US120326x3N	WTH-165/B/1P-385 x3pcs +NPE	US120316x3N
WTH-165/B/R/1P-420 x3pcs +NPE	US120327x3N	WTH-165/B/1P-420 x3pcs +NPE	US120317x3N

### 1P + NPE Combintion Package

Model with suffix	Ordering Code	Model with suffix	Ordering Code
WTH-165/B/R/1P-275 +NPE	US120324x1N	WTH-165/B/1P-275 +NPE	US120314x1N
WTH-165/B/R/1P-320 +NPE	US120325x1N	WTH-165/B/1P-320 +NPE	US120315x1N
WTH-165/B/R/1P-385 +NPE	US120326x1N	WTH-165/B/1P-385 +NPE	US120316x1N
WTH-165/B/R/1P-420 +NPE	US120327x1N	WTH-165/B/1P-420 +NPE	US120317x1N



## Surge Protective Device

---

### FAQ & Help

1. What should I do if I can't find the paper manual in the product packaging?

Watchful Eye products is committed to going green with paperless data sheets. On the side of each product enclosure is an engraved link with URL for downloading paperless data sheet and QR code of the website. If you need the paper data sheet, you can open the link and print the data sheet by yourself.

2. The advantages of fault indication windows?

If surge protection fails, the fault indication windows will turn red, thus it can be seen intuitively, and the surge protective device can be replaced in time to avoid damage to the equipment caused by a second surge.

3. What instruments can be used to test whether its surge protection function is normal or not?

Test with a Watchful Eye surge protector tester

4. Can you list more applications?

Power supply panel, whole house



## Surge Protective Device

---

### Download WatchfulEye Official App

To learn about more products and updates from company, please scan QR code to download the official App:



---

### After-sale Services

Watchful Eye provides a 5-year quality warranty globally.

[I have a question](#)